

**PRODUCT: 1 PLY SILICONE/FIBERGLASS HOSE**  
**PRODUCT CODE: H-SILFIB-1-X**

**Product Description**

SUITABLE FOR STATIONARY TO LOW FLEXING HIGH TEMPERATURE EXHAUST CONTROL.

**Suitable Applications**

Application	Suitability Rating
MEDIUM PRESSURE AIR-HANDLING	-
HANDLING OF HOT AIR AND COMBUSTION BY-PRODUCTS	-
STATIONARY TO LOW FLEX HIGH TEMP EXHAUST CONTROL	-

**Temperature Ratings**

Max. Temperature	Max. Intermit. Temperature	Min. Temperature
650.0	-	-60.0

**Standard Lengths**

Max. Length	Min. Length	Standard Lengths	Available Lengths
-	-	25.0	-

**Available Diameters**

Available Diameters	Increments of
2" TO 24"	1.0

**Characteristics**

**Tube**

Tube Type	Tube Name	Description	Recommendation	Gauge
FIBERGLASS	INNER LAYER	-	-	-
SILICONE	COATING	-	-	-

**Wire**

Outer Wire	Inner Wire	Inner Gauge	Outer Gauge	External Wire	Encapsulated Wire	Wearstrip	Grounding Wire	Integral Wire
	HIGH TEMP BONDED			-	Yes	-	-	-



**PRODUCT: 2 PLY SILICONE/FIBERGLASS HOSE**  
**PRODUCT CODE: H-SILFIB-2-X**

**Product Description**

A POPULAR STYLE FOR STATIONARY OR LOW MOVEMENT HIGH TEMPERATURE EXHAUST CONTROL APPLICATIONS.

**Suitable Applications**

Application	Suitability Rating
STATIONARY TO LOW FLEX HIGH TEMP EXHAUST CONTROL	-
MEDIUM PRESSURE AIR-HANDLING	-
HANDLING OF HOT AIR AND COMBUSTION BY-PRODUCTS	-

**Temperature Ratings**

Max. Temperature	Max. Intermit. Temperature	Min. Temperature
650.0	-	-60.0

**Standard Lengths**

Max. Length	Min. Length	Standard Lengths	Available Lengths
-	-	12.0	-

**Available Diameters**

Available Diameters	Increments of
2" TO 24"	1.0

**Tube**

Tube Type	Tube Name	Description	Recommendation	Gauge
FIBERGLASS	INNER LAYER	-	-	-
FIBERGLASS	OUTER LAYER	-	-	-
SILICONE	COATING	-	-	-

**Wire**

Outer Wire	Inner Wire	Inner Gauge	Outer Gauge	External Wire	Encapsulated Wire	Wearstrip	Grounding Wire	Integral Wire
	HIGH TEMP BONDED			-	Yes	-	-	-



CUSTOMER:  
 CUSTOMER P.O.:  
 PROJECT:  
 ENGINEER:  
 SALES REP.:  
 IDENTIFICATION / TAGGING:



The device depicted and described hereon embodies proprietary information owned by the manufacturer. All design, manufacturing, reproduction, sales and patent rights regarding this device or drawing reserved except where explicit right is guaranteed in writing. We reserve the right to make design changes.

Drawn by: Janos B  
 Date: 9/22/2010  
 Scale: NTS  
 Weight: N/A

**(16-04) HRHT-650 Vehicle Exhaust - Vehicle Emissions Hose reels (650°F)**  
**Specification Drawing**  
 Drawing No.: -  
 Material: -  
 File Name: (16-04) VE High Temp Hose -  
 Sheet: 1/2

**PRODUCT: 2 PLY REINFORCED SILICONE/NOMEX HOSE**  
**PRODUCT CODE: H-SILNOM-2-x**

**Product Description**

COMBINED WITH AN ENCAPSULATED REINFORCEMENT THIS DUCT IS IDEAL FOR USE IN CONSTANT FLEXING APPLICATIONS OR WITH HOSE REELS.

**Suitable Applications**

Application	Suitability Rating
GENERAL SERVICE	-
HIGH TEMPERATURE AIR MOVEMENT	-
GARAGE FUME CONTROL W/CONSTANT FLEXING	-
HOSE REELS	-

**Temperature Ratings**

Max. Temperature	Max. Intermit. Temperature	Min. Temperature
650.0	-	-60.0

**Standard Lengths**

Max. Length	Min. Length	Standard Lengths	Available Lengths
-	-	24.0	-

**Available Diameters**

Available Diameters	Increments of
2" TO 24"	1.0

**Tube**

Tube Type	Tube Name	Description	Recommendation	Gauge
REINFORCED SILICONE/NOMEX	INNER LAYER	-	-	-
REINFORCED SILICONE/NOMEX	OUTER LAYER	-	-	-

**Wire**

Outer Wire	Inner Wire	Inner Gauge	Outer Gauge	External Wire	Encapsulated Wire	Wearstrip	Grounding Wire	Integral Wire
	HIGH TEMP BONDED			-	Yes	-	-	-



**MODELS & OPTIONS**

**Main System / Part**

- [SNH-10](#) 10" dia, 2ply Silicone/Nomex hose 650deg F - Suitable for use in constant flexing applications or with hose reels (per foot)
- [SNH-12](#) 12" dia, 2ply Silicone/Nomex hose 650deg F - Suitable for use in constant flexing applications or with hose reels (per foot)
- [SNH-14](#) 14" dia, 2ply Silicone/Nomex hose 650deg F - Suitable for use in constant flexing applications or with hose reels (per foot)
- [SNH-4](#) 4" dia, 2ply Silicone/Nomex hose 650deg F - Suitable for use in constant flexing applications or with hose reels (per foot)
- [SNH-5](#) 5"dia 2 ply Silicone/Nomex 650deg F - Suitable for use in constant flexing applications or with hose reels (per foot)
- [SNH-6](#) 6"dia 2 ply Silicone/Nomex hose 600deg F - suitable for use in constant flexing applications or with hose reels (per foot)
- [SNH-8](#) 8" Ø 2 ply Silicone/Nomex hose 650°F - suitable for use in constant flexing applications or with hose reels (Sold Per Foot)

**Hose Clamps**

- [HCS-10](#) Hose Clamps 10" (250mm) Ø
- [HCS-12](#) Hose Clamps 12" (315mm) Ø
- [HCS-14](#) Hose Clamps 14" (350mm)Ø
- [HCS-4](#) Hose Clamps 4" (100mm) Ø
- [HCS-5](#) Hose Clamps 5" (125mm) Ø
- [HCS-6](#) Hose Clamps 6" (150mm) Ø
- [HCS-8](#) Hose Clamps 8" (200mm) Ø

CUSTOMER:  
 CUSTOMER P.O.:  
 PROJECT:  
 ENGINEER:  
 SALES REP.:  
 IDENTIFICATION / TAGGING:

[www.lev-co.com](http://www.lev-co.com) • 1.888.862.5356



The device depicted and described hereon embodies proprietary information owned by the manufacturer. All design, manufacturing, reproduction, sales and patent rights regarding this device or drawing reserved except where explicit right is guaranteed in writing. We reserve the right to make design changes.

Drawn by: Janos B  
 Date: 9/22/2010  
 Scale: NTS  
 Weight: N/A

**(16-04) HRHT-650 Vehicle Exhaust - Vehicle Emissions Hose reels (650°F)**  
**Specification Drawing**

Drawing No.: -      File Name: (16-04) VE High Temp Hose -  
 Material: -      Sheet: 2/2