



## KANADUCT

**Temp. Range:**  
-13iF to 180iF

**Applications:**  
General ducting and blower hose used for spot coolers, clean room venting, fume/dust removal, elbows for rigid pipe

**Construction:**  
Interlocked polypropy

<b>I.D. (Inches)</b>	2-1/2	3	4	5	6	8	10	12
<b>O.D. (Inches)</b>	2.80	3.23	4.20	5.20	6.16	8.06	10.21	12.07
<b>Min. Bending Radius 72°F (Inches)</b>	6.00	7.00	11.00	14.00	15.00	20.00	27.00	32.00
<b>Weight, Lbs/Ft</b>	0.35	0.36	0.52	0.76	0.79	1.07	1.52	1.68

CUSTOMER:	
CUSTOMER PO:	
PROJECT:	
ENGINEER:	
IDENTIFICATION/TAGGING:	

The device depicted and described hereon embodies proprietary information owned by the manufacturer. All design, manufacturing, reproduction, sales and patent rights regarding this device or drawing are reserved except where explicit right is granted in writing. We reserve the right to make design changes.

lev-co	THE LOCAL EXHAUST & VENTILATION COMPANY	1050 Brock Road Pickering, ON L1W 3X4 905.831.7001 E-Mail: Sales@LEV-CO.com
	NORTH AMERICA: 888.862.5356, FAX 866.840.9923 TORONTO MONTREAL OTTAWA EDMONTON LONDON WINDSOR	
DRAWN BY: SL	TITLE: Kanaduct	Page 1 of 1
DATE: 03/26/01		
SCALE: NTS	MODEL: Kanaduct-x	